



## Model Name **RP6503**


### Unique selling point

- \* High performance 8 core A73\*4+A53\*4, 8GB memory, 64GB storage, and Android 11 OS.
- \* Germ-Resistant Screen + pen + I/O \* Temperature/Humidity/Particle/TVOC sensor \*Hardware Low blue light - no color change
- \* Ezwrite 6.0 whiteboard support URL / YouTube / scalable canvas / hand recognition (30 language / [Google translate \(59 language\)](#) / Camera as visualizer /
- \* Wireless mirroring contents of Window/Mac/iOS/Android/Chrome to screen and mirror screen contents to unlimited mobile devices, 9 devices mirroring simultaneously; Moderator mode for annotation/touch/host control in mirroring; Smart control
- \* Support floating window mirroring act like PIP. Miracast with Touch back function in Window.
- \* Support multi window: opening 5 android app and 1 input showing in IFP at the same time
- \* Array mic with beamforming x 8 + HiFi 2.1 sound system + Type C display+ touch input
- \* Account management system (AMS) provides personalized workspace, [link up to your Google drive / Dropbox / OneDrive / Network drive](#); Able to lock down IFP (keylock/IR lock/screen lock) before user login AMS for security control
- \* Built in [lifetime cloud base X sign broadcast system](#) (Microsoft office, Youtube live, etc.) and Device Management System
- \* Education software: Kahoot! / Seesaw / Kevin Bradford 10 Games / Math Tutors / Ezwrite 6.0 PC version / Snowflake (optional)


Panel	Screen Diagonal	65"	
	Backlight	DLED	
	Resolution	3840 x 2160	
	Aspect Ratio	16 : 9	
	Brightness	400nits	
	Contrast Ratio / Dynamic Contrast Ratio	1200:1 / 30,000:1	
	Viewing Angle	178 degree (H) / 178 degree (V)	
	Color gamut (x% NTSC)	72%	
	Frame Rate	60Hz	
	Response Time	8ms	
	Panel bit	10-bit	
Light life	50,000hrs		
Touch solution	Touch tech.	IR	
	Number of touches	Up to 40 Point Multi-touch in Window / 32 Point in Android	
	Touch interface	Type B USB x 3	
	Resolution	32767 x 32767	
Cover glass	Thickness	Tempered, 3.2 mm (Same hardness with much clear image and less reflection)	
	Hardness	9H	
	Germ resistance	Yes (SIAA/ TUV Test Confirmed / JIS Z 2801:2010) - glass / pen / remote / front input	
Speaker	Built-in speaker	Built-in speakers 16W x 2 & subwoofer 16W x 1 (Certified by Dobby Digital+)	
Interface	Input	Power (AC) Inlet	x 1
		D-Sub	x 1
		HDMI	x 3 (2.0 x 3)
		DP	x 1 (1.2a x 1)
		USB Type A	x 7 (USB 3.0 x 5 + USB 2.0 x 2) / Dedicated USB port for camera
		USB Type C	x 2 (USB 3.0 x 2)
		Mic in (3.5mm)	x 2 (Front and back)
		LAN (In / out)	x 2
	Output	HDMI	x 1 (2.0 x 1)
		Line out (3.5mm)	x 1
		SPDIF	x 1
	Others	Array Microphone	x 8
		NFC Reader	x 1
		Motion Sensor	x 1
		Air Ionizer	x 1
		Air Quality Sensor / Light Sensor	x 1 / x 1
		IR receiver	x 1
OPS Slot	x 1 (OTG to Android memory)		
Mechanical	Dimension (WxHxD) (Without Packing / With Packing)	1489.3 x 934.3 x 121.5mm / 1660 x 1045 x 220 mm	
	Net Weight/Gross Weight	43 Kg / 56 Kg ± 1.5Kg	
Power	Power supply	AC100 to 240V, 50 to 60 Hz	
	Power consumption	425W (max.) / <0.5W (Standby)	
OSD	On-Screen Display Languages	English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified Chinese / Arabic / Japanese / Thai / Persian / Vietnamese / Korean / Turkish / Indonesian / Hebrew (28L)	
Accessories	Standard	Remote Control	x 1
		Power Cord / VGA / HDMI	x 1 / x 1 / x 1
		Touch pen	x 2
		Touch Cable (USB to USB)	x 1
		Type C Cable	x 1
		Wall mount	x 1

# Input/output terminals

## Front I/O



## Rear I/O




## Camera USB port



## WiFi dongle & Remote controller USB port



## Wallmount



## Dimension

