

2326 | 2026-2

Centralised office shredders with 260 mm feed opening, high sheet capacity and powerful but quiet motor for continuous operation. The patented ECC - Electronic Capacity Control indicates the used sheet capacity during the shredding process in order to avoid paper jams.

EBA 2326 S | C | CC | CCC

SPS – Safety Protection System as described on pages 8 | 9. Multifunction control element EASY-SWITCH with integrated optical indicators for the operational status of the shredder. Automatic start / stop via a photo cell. ECC – Electronic Capacity Control: patented indication of the used sheet capacity during shredding process. High-quality cutting shafts from special hardened steel, paper clip proof for models 2326 S and C. Lifetime guarantee on the cutting shafts under conditions of fair wear and tear (except EBA 2326 CC with 0.8 x 12 mm and EBA 2326 CCC with 0.8 x 5 mm micro cut). EBA 2326 S and EBA 2326 C suitable for safe shredding of the most common CDs and DVDs. Powerful 640 Watt single phase motor for continuous operation. Sturdy "Twin Drive System" with fully closed gear box housing. High-quality wooden cabinet with a cabinet volume of 125 litres. Movable on castors. Environmentally-friendly shred bin with 100 litres volume for the shreds (no disposable shred bags required). Attractive colour combination silver / dark grey.

EBA 2026-2 CCC

This high-security shredder with 0.8 x 5 mm micro cut comes with all operational features as described above. In addition this model is equipped with an automatic oil injection system, which lubricates the cutting shafts when shredding and guarantees a consistently high shred performance. The especially powerful and quiet 1300 watt motor in combination with the high shred speed provide a remarkable output capacity.

Outstanding safety features: SPS includes an electronically controlled, patented safety flap in the feed opening.



Intelligent control via the multifunction control element EASY-SWITCH with illuminated symbols for the operational status of the shredder.



ECC Electronic Capacity Control – LEDs indicate the used sheet capacity during the shredding process to avoid paper jams.



	EBA 2326 S	EBA 2326 C	EBA 2326 C	EBA 2326 CC	EBA 2326 CCC	EBA 2026-2 CCC
Insertion width in mm	260	260	260	260	260	260
Cutting width in mm	4	4 x 40	2 x 15	0.8 x 12	0.8 x 5	0.8 x 5
Sheet capacity (A4, 70 g/sqm)	30-32	25-27	15-17	8-10	5-7	8-9
Sheet capacity (A4, 80 g/sqm)	26-28	21-23	13-15	6-8	4-6	7-8
DIN security level	P-2	P-4	P-5	P-6	P-7	P-7
Motor capacity in watt	640	640	640	640	640	1300
Shred bin volume in litres	100	100	100	100	100	100
Dimensions W x D x H in mm	495 x 470 x 926	495 x 470 x 926	495 x 470 x 926	495 x 470 x 926	495 x 470 x 926	495 x 470 x 926
Weight in kg	48	48	48	48	48	48



Model 2026-2 CCC: The automatic oil injection system lubricates the cutting shafts when shredding and guarantees a consistently high shred performance.

