

Entry level machine from the Professional range. For entire departments or office floors.

- Also shreds credit cards and store cards as well as CDs and discs (see table for details)
- Intake width: 330 mm
- Available as strip-cut version in security level 2
- Available as particle-cut version in security levels 3, 4, 5 and HS level 6
- Container/collection volume: 145 l
- Device height: 936 mm
- Automatic reverse in the event of a paper jam
- EMCS (energy management and control system): automatic shutdown function, automatic switch-off, permanent mode
- Folding safety element with contact protection and integrated service flap
- Automatic oiler for particle-cut version
- Mobile on rollers
- Option: separate CD cutting unit for shredding CDs and DVDs in two versions:
 - For particle size 3.9 x 40 mm
 - In high security OMDD (particle size 2.2 x 4 mm); for highest security requirements. Recommended by the Federal Office for Information Security (BSI)
- Option: metal detection – protects the cutting unit against accidental metallic material damage



HSM SECURIO P36



Intelligent multi-function control key and 8 function displays – e.g. for metal detection.



Folding safety element with contact protection and integrated service flap.



A separate CD cutting unit (also suitable for discs) is optionally available for the HSM SECURIO P36.



Special CD waste container for separating and sorting the shredded material (optional).

Model	HSM SECURIO P36		HSM SECURIO P36			
	Strips	Strips	Particles	Particles	Particles	Particles
Cutting type	Strips	Strips	Particles	Particles	Particles	Particles
Cutting size in mm	5.8	3.9	4.5 x 30	1.9 x 15	0.78 x 11	1 x 5
Security level DIN 32757-1	2	2	3	4	5	HS level 6
Cutting capacity* in 70 g/m ² sheets	47–49	37–39	29–31	18–20	11–12	9
Cutting capacity* in 80 g/m ² sheets	39–41	31–33	25–27	15–17	10–11	7
Cutting speed in mm/s	90	90	100	100	100	100
Intake width in mm	330	330	330	330	330	330
Motor	1600 W	1600 W	1600 W	1600 W	1600 W	1600 W
Voltage / frequency	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz
Size (W x D x H) in mm	580x550x936	580x550x936	580x550x936	580x550x936	580x550x936	580x550x936
Weight in kg	64	64	68	68	68	68
Container/collection volume in litres	145	145	145	145	145	145
Suitable for paper and						

* max. per cycle with DIN A4, 70 g/m² or DIN A4, 80 g/m²

All technical data and dimensions are approximate values. Technical and design modifications reserved.

High capacity model from the SECURIO range for busy departments and office floors.

- Also shreds credit cards and store cards as well as CDs and discs (see table for details)
- Intake width: 330 mm
- Available as strip-cut version in security level 2
- Available as particle-cut version in security levels 3, 4, 5 and HS level 6
- Container/collection volume: 145 l
- Device height: 936 mm
- Automatic reverse in the event of a paper jam
- EMCS (energy management and control system): automatic shutdown function, automatic switch-off, permanent mode
- Folding safety element with contact protection and integrated service flap
- Automatic oiler for particle-cut version
- Mobile on rollers
- Option: separate CD cutting unit for shredding CDs and DVDs in two versions:
 - For particle size 3.9 x 40 mm
 - In high security OMDD (particle size 2.2 x 4 mm); for highest security requirements. Recommended by the Federal Office for Information Security (BSI)
- Option: metal detection – protects the cutting unit against accidental metallic material damage



HSM SECURIO P40



A separate CD cutting unit is optionally available for the HSM SECURIO P40.



Intelligent multi-function control key and 8 function displays – e. g. for metal detection.



The automatic oiler ensures a consistent cutting capacity and quality for the particle-cut version.



Folding safety element with contact protection and integrated service flap.

Model	HSM SECURIO P40		HSM SECURIO P40			
	Strips	Strips	Particles	Particles	Particles	Particles
Cutting type	Strips	Strips	Particles	Particles	Particles	Particles
Cutting size in mm	5.8	3.9	4.5 x 30	1.9 x 15	0.78 x 11	1 x 5
Security level DIN 32757-1	2	2	3	4	5	HS level 6
Cutting capacity* in 70 g/m ² sheets	58–60	45–47	35–37	22–24	13–14	10
Cutting capacity in * 80 g/m ² sheets	51–53	40–42	31–33	18–20	12–13	8
Cutting speed in mm/s	100	100	110	110	110	110
Intake width in mm	330	330	330	330	330	330
Motor	2100 W	2100 W	2100 W	2100 W	2100 W	2100 W
Voltage / frequency	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz	230 V/50 Hz
Size (W x D x H) in mm	580x550x936	580x550x936	580x550x936	580x550x936	580x550x936	580x550x936
Weight in kg	67	67	72	72	72	72
Container/collection volume in litres	145	145	145	145	145	145
Suitable for paper and						

* max. per cycle with DIN A4, 70 g/m² or DIN A4, 80 g/m²

All technical data and dimensions are approximate values. Technical and design modifications reserved.