












Model	HSM SECURIO C18		HSM SECURIO C18	
Cutting type	Strips	Strips	Particles	Particles
Cutting size in mm	5.8	3.9	3.9 x 30	1.9 x 15
Security level DIN 32757-1	2	2	3	4
Cutting capacity* in 70 g/m <sup>2</sup> sheets	19-20	15-16	10-11	8-9
Cutting capacity* in 80 g/m <sup>2</sup> sheets	15-16	11-12	8-9	6-7
Cutting speed in mm/s	45	45	45	45
Intake width in mm	230	230	230	230
Motor	400 W	400 W	400 W	400 W
Voltage / frequency	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Size (W x D x H) in mm	395 x 317 x 605	395 x 317 x 605	395 x 317 x 605	395 x 317 x 605
Weight in kg	4.6	4.6	5.2	5.2
Container/collection volume in litres	25	25	25	25
Suitable for paper and	  	 	 	 

\* max. per cycle with DIN A4, 70 g/m<sup>2</sup> or DIN A4, 80 g/m<sup>2</sup>

All technical data and dimensions are approximate values. Technical and design modifications reserved.

## **High-performance entry-level model for personal use.**

- Also shreds credit cards, customer cards and CDs (see bottom right for details)
- Intake width: 230 mm
- Available as strip-cut version in security level 2
- Available as particle-cut version in security levels 3 and 4
- Removable waste container: 25 l
- Device height: 605 mm
- Automatic start/stop function
- Automatically stops when the shredded material container is full or is removed
- Automatic reverse in the event of a paper jam
- ZES (zero energy standby) for zero power consumption in standby mode

**WORLD TRADE**




For  
sales and service  
Please Call

Tel: 2861 3823 Fax: (852) 2528 1370

## **HSM SECURIO C18**



Removable container for the convenient removal of shredder material.



HSM lifetime warranty on the solid steel cutting rollers: the HSM warranty for the entire service life of the product.



With the multifunctional button, you can select the different function modes: start, stop and permanent mode.



Folding safety element with contact protection (the machine stops when pressure is applied to the element).