

TECH SPEC JABRA PRO 900 SERIES

Product Name	Jabra PRO 920	Jabra PRO 930	Jabra PRO 925	Jabra PRO 935
Packaging dimensions (L x W x H)	Mono master carton: 600 x 399 x 316mm Mono unit box: 185 x 138.5 x 67.5mm Duo master carton: 600 x 399 x 235mm Duo unit box: 190 x 191 x 65mm	Mono master carton: 600 x 399 x 316mm Mono unit box: 185 x 138.5 x 67.5mm Duo master carton: 600 x 399 x 235mm Duo unit box: 190 x 191 x 65mm	Master carton: 600 x 399 x 316mm Unit box: 185 x 138.5 x 67.5mm	Master carton: 600 x 399 x 316mm Unit box: 185 x 138.5 x 67.5mm
Main unit dimension (L x W x H)	Base: 118 x 76 x 29mm Mono headset: 131 x 50 x 18mm Duo headset: 165 x 165 x 30mm	Base: 118 x 76 x 29mm Mono headset: 131 x 50 x 18mm Duo headset: 165 x 165 x 30mm	Base: 118 x 76 x 29mm Headset: 131 x 50 x 18mm	Base: 118 x 76 x 29mm Headset: 131 x 50 x 18mm
Weight	Base: 177g Mono headset: 29g Duo headset: 80g	Base: 165g Mono headset: 29g Duo headset: 80g	Base: 177g Headset: 29g	Base: 165g Headset: 29g
What's in the box	1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. USB cable (PRO 930 & 935 only) 9. Flat cable (PRO 920 & 925 only)	1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. USB cable (PRO 930 & 935 only) 9. Flat cable (PRO 920 & 925 only)	1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. USB cable (PRO 930 & 935 only) 9. Flat cable (PRO 920 & 925 only)	1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. USB cable (PRO 930 & 935 only) 9. Flat cable (PRO 920 & 925 only)
Battery included	Yes	Yes	Yes	Yes
Charging time	180 min	180 min	180 min	180 min
AC power supply	Yes	Yes	Yes	Yes
Certifications	CE, CB, FCC, IC, NOM, NTC, EAC, PSB, ICASA, SIRIM, ACMA, NZ Telepermit, UL, TCO	CE, CB, FCC, IC, NOM, NTC, EAC, PSB, ICASA, SIRIM, ACMA, NZ Telepermit, UL, TCO	CE, FCC, IC, UL, SRRC, TELEC, EAC, NCC, IDA, RoHS, Reach, KCC, ETA, ACMA, EMC, SIRIM, NTC, DGPosTel	CE, FCC, IC, UL, SRRC, TELEC, EAC, NCC, IDA, RoHS, Reach, KCC, ETA, ACMA, EMC, SIRIM, NTC, DGPosTel
Warranty	North America: 1 year limited warranty Europe/APAC: 2 year limited warranty	North America: 1 year limited warranty Europe/APAC: 2 year limited warranty	North America: 1 year limited warranty Europe/APAC: 2 year limited warranty	North America: 1 year limited warranty Europe/APAC: 2 year limited warranty
Bluetooth® device	N/A	N/A	Yes	Yes
DECT Device	Yes	Yes	N/A	N/A
NFC	N/A	N/A	Yes (only on Dual connectivity)	Yes (only on Dual connectivity)
Operating range	Up to 120m/395ft	Up to 120m/395ft	Up to 100 meter/330ft	Up to 100 meter/330ft
Headset bandwidth	Narrowband and Wideband	Narrowband and Wideband	Narrowband and Wideband	Wideband only
Connection (mini jack, USB, etc)	Mini USB, RJ-9 for handset, RJ-9 for phone body, RJ-45 for AUX	Mini USB	Mini USB, RJ-9 for handset, RJ-9 for phone body, RJ-45 for AUX	Mini USB
Talk time	Up to 12 hours	Up to 12 hours	Up to 12 hours	Up to 12 hours
Standby time	Up to 33 hours	Up to 33 hours	Up to 7 days	Up to 7 days
What is Bluetooth® wireless technology	N/A	N/A	Bluetooth® version 4.0	Bluetooth® version 4.0
Speaker size	Mono: Ø 28 x 5.9mm Duo: Ø 23 x 6.2mm	Mono: Ø 28 x 5.9mm Duo: Ø 23 x 6.2mm	Ø 28 x 5.9mm	Ø 28 x 5.9mm
Speaker sensitivity	91±3dB (60mV at 1000Hz)	91±3dB (60mV at 1000Hz)	91±3dB (60mV at 1000Hz)	91±3dB (60mV at 1000Hz)
Speaker impedance	Mono: 32±4.8Ω (at 1000Hz) Duo: 64±1.5% Ohm at 1000Hz	Mono: 32±4.8Ω (at 1000Hz) Duo: 64±1.5% Ohm at 1000Hz	32±4.8Ω (at 1000Hz)	32±4.8Ω (at 1000Hz)
Speaker max output power	Mono: Max input Power 20mW at 0.8V Duo: Not specified	Mono: Max input Power 20mW at 0.8V Duo: Not specified	Max input Power 20mW at 0.8V	Max input Power 20mW at 0.8V
Speaker frequency range	Mono: 150Hz to 7 kHz (at output S.P.L. -10dB) Duo: 180Hz to 7 kHz	Mono: 150Hz to 7 kHz (at output S.P.L. -10dB) Duo: 180Hz to 7 kHz	150Hz to 7 kHz (at output S.P.L. -10dB)	150Hz to 7 kHz (at output S.P.L. -10dB)
Microphone type	Uni-directional Microphone	Uni-directional Microphone	Uni-directional Microphone	Uni-directional Microphone
Microphone sensitivity	-30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa)	-30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa)	-30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa)	-30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa)
Microphone frequency range	100Hz to 10kHz			

Extended Info

Supported Bluetooth® profiles	N/A	A2DP (v1.2), Handsfree Profile (v1.6), Headset Profile (v1.2), AGHFP (v1.6)
Bluetooth® compliance	N/A	Yes

TECH SPEC JABRA PRO 900 SERIES

Product Name	Jabra PRO 920	Jabra PRO 930	Jabra PRO 925	Jabra PRO 935
Bluetooth® wireless technology	N/A	N/A	Bluetooth® Class 1 (only on Dual connectivity)	Bluetooth® Class 1 (only on Dual connectivity)
Speaker bandwidth Speak mode	20Hz-4.5kHz	20Hz-4.5kHz	Not specified	Not specified
USB Cord length	1.5m	1.5m	1.5m	1.5m
Operating temperature	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)
Storage temperature	-20°C to 45°C (-4°F to 113°F)	-20°C to 45°C (-4°F to 113°F)	-20°C to 45°C (-4°F to 113°F)	-20°C to 45°C (-4°F to 113°F)
Supported modes	N/A	N/A	SCO, eSCO, Sniff mode	SCO, eSCO, Sniff mode
Security	DSAA + DSC	DSAA + DSC	Authentication and Encryption (Bluetooth® standard)	Authentication and Encryption (Bluetooth® standard)
Power consumption	7.5V/650mA	7.5V/650mA	7.5V/650mA	7.5V/650mA
Current consumption microphone	70 to 150 uA	70 to 150 uA	70 to 150 uA	70 to 150 uA
Battery status % after 30 min/60 min	25% after 30 min and 50% after 60 min	25% after 30 min and 50% after 60 min	25% after 30 min and 50% after 60 min	25% after 30 min and 50% after 60 min
Charging plug dimensions	Ø 2.35mm			
Material used	Polycarbonate/ Akrylonitril-butadien-styren (PC/ABS): CYCOLOY C1200HF, GY6A288 Thermoplastic Polyurethanes - TPU: Desmopan 445 Acetal (POM) Copolymer: POM Tepcon M90 Thermoplastic acetal homopoly: DELRIN 500 P Polybutylene Terephthalate (PBT): PBT S600F20 Thermoplastic Elastomer (TPE): TPE Hytrel 4069 Thermoplastic Elastomer (TPE): TPE Hytrel 3548 Polypropylene (PP): AV161 Thermoplastic vulcanizates (TPVs): Santoprene TPV 201-87 Silicone rubber: KE-931TU			
Pairing PIN	N/A	N/A	0000	0000
Features	Crystal Clear Sound HD Voice – Wideband Audio Jabra Software Applications Noise Canceling Microphone PeakStop™ Remote Asset Management Remote Call Control SafeTone™ Talk in Comfort Up to 120 Meter/395ft Wireless Freedom (PRO 920 & 930) Up to 100 Meter/330ft Wireless Freedom (PRO 925 & 935) 8-Hour Battery Life UC Plug-And-Play (PRO 935 & 930)			

ITEM NUMBER	DESCRIPTION 1	DESCRIPTION 2	EAN	UPC
920-25-508-101	Jabra PRO 920, EMEA	1.88-1.9 GHz EU standard DECT	5706991013566	
920-25-508-101JPM	Jabra PRO 920, EMEA JPM	Range set to Very Low	5706991018516	
920-25-508-102	Jabra PRO 920, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991013573	
920-25-508-102JPM	Jabra PRO 920, UK JPM	Range set to Very Low	5706991018509	
920-25-508-103	Jabra PRO 920, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991013580	
920-29-508-101	Jabra PRO 920 Duo, EMEA	1.88-1.9 GHz EU standard DECT	5706991018318	
920-29-508-102	Jabra PRO 920 Duo, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991018325	
920-29-508-103	Jabra PRO 920 Duo, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991018332	
920-65-508-105	Jabra PRO 920, NA	1.92-1.93 GHz US DECT 6.0	5706991013597	706487012795
920-69-508-105	Jabra PRO 920 Duo, NA	1.92-1.93 GHz US DECT 6.0	5706991018349	706487016175
930-25-503-101	Jabra PRO 930 MS, EMEA	1.88-1.9 GHz EU standard DECT	5706991013603	
930-25-503-102	Jabra PRO 930 MS, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991013610	
930-25-503-103	Jabra PRO 930 MS, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991013627	
930-25-509-101	Jabra PRO 930, EMEA	1.88-1.9 GHz EU standard DECT	5706991013634	
930-25-509-101JPM	Jabra PRO 930, EMEA JPM	Range set to Very Low	5706991018530	
930-25-509-102	Jabra PRO 930, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991013641	
930-25-509-102JPM	Jabra PRO 930, UK JPM	Range set to Very Low	5706991018523	
930-25-509-103	Jabra PRO 930, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991013658	
930-29-503-101	Jabra PRO 930 Duo MS, EMEA	1.88-1.9 GHz EU standard DECT	5706991018356	
930-29-503-102	Jabra PRO 930 Duo MS, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991018363	
930-29-503-103	Jabra PRO 930 Duo MS, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991018370	
930-29-509-101	Jabra PRO 930 Duo, EMEA	1.88-1.9 GHz EU standard DECT	5706991018387	
930-29-509-102	Jabra PRO 930 Duo, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991018394	

ITEM NUMBER	DESCRIPTION 1	DESCRIPTION 2	EAN	UPC
930-29-509-103	Jabra PRO 930 Duo, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991018400	
930-65-503-105	Jabra PRO 930 MS, NA	1.92-1.93 GHz US DECT 6.0	5706991013665	706487012801
930-65-509-105	Jabra PRO 930, NA	1.92-1.93 GHz US DECT 6.0	5706991013672	706487012818
930-69-503-105	Jabra PRO 930 Duo MS, NA	1.92-1.93 GHz US DECT 6.0	5706991018417	706487016199
930-69-509-105	Jabra PRO 930 Duo, NA	1.92-1.93 GHz US DECT 6.0	5706991018424	706487016182
925-15-508-106	Jabra PRO 925, China	Single Connectivity	5706991016611	706487014607
925-15-508-107	Jabra PRO 925, Korea	Single Connectivity	5706991016628	706487014614
925-15-508-182	Jabra PRO 925, HK, SG, MY, IN, ID	Single Connectivity	5706991016635	706487014621
925-15-508-182 IN	Jabra PRO 925, IN	Single Connectivity	5706991019445	
925-15-508-185	Jabra PRO 925, JP,TW,TH,PH,VN,NA	Single Connectivity	5706991016642	706487014638
925-15-508-201	Jabra PRO 925 BT, EMEA	Dual Connectivity	5706991016659	706487014645
925-15-508-202	Jabra PRO 925 BT, UK, HK, SG	Dual Connectivity	5706991016666	706487014652
925-15-508-203	Jabra PRO 925 BT, AU, NZ	Dual Connectivity	5706991016673	706487014669
925-15-508-205	Jabra PRO 925 BT, NA	Dual Connectivity	5706991016680	706487014676
925-15-508-206	Jabra PRO 925 BT - CN	Dual Connectivity	5706991017496	
925-15-508-207	Jabra PRO 925 BT - KR	Dual Connectivity	5706991017502	
935-15-503-106	Jabra PRO 935 MS, China	Single Connectivity	5706991016697	706487014683
935-15-503-107	Jabra PRO 935 MS, Korea	Single Connectivity	5706991016703	706487014690
935-15-503-182	Jabra PRO 935 MS, HK, SG, MY, IN, ID	Single Connectivity	5706991016710	706487014706
935-15-503-182 IN	Jabra PRO 935 MS, IN	Single Connectivity	5706991019452	
935-15-503-185	Jabra PRO 935 MS, JP,TW,TH,PH,VN,-	Single Connectivity	5706991016727	706487014713
935-15-503-201	Jabra PRO 935 MS, BT, EMEA	Dual Connectivity	5706991016734	706487014720
935-15-503-202	Jabra PRO 935 MS, BT, UK, HK, SG	Dual Connectivity	5706991016741	706487014737
935-15-503-203	Jabra PRO 935 MS, BT,AU, NZ	Dual Connectivity	5706991016758	706487014744
935-15-503-205	Jabra PRO 935 MS, BT, NA	Dual Connectivity	5706991016765	706487014751
935-15-503-206	Jabra PRO 935 MS BT - CN	Dual Connectivity	5706991017533	
935-15-503-207	Jabra PRO 935 MS BT - KR	Dual Connectivity	5706991017540	
935-15-509-106	Jabra PRO 935, CN	Single Connectivity	5706991016772	706487014768
935-15-509-107	Jabra PRO 935 Korea	Single Connectivity	5706991016789	706487014775
935-15-509-182	Jabra PRO 935, HK, SG, MY, IN, ID	Single Connectivity	5706991016796	706487014782
935-15-509-182 IN	Jabra PRO 935, IN	Single Connectivity	5706991019469	
935-15-509-185	Jabra PRO 935, JP,TW,TH,PH,VN,NA	Single Connectivity	5706991016802	706487014799
935-15-509-201	Jabra PRO 935 BT, EMEA	Dual Connectivity	5706991016819	706487014805
935-15-509-202	Jabra PRO 935, BT, UK,HK,SG	Dual Connectivity	5706991016826	706487014812
935-15-509-203	Jabra PRO 935 BT, AU, NZ	Dual Connectivity	5706991016833	706487014829
935-15-509-205	Jabra PRO 935 BT, NA	Dual Connectivity	5706991016840	706487014836
935-15-509-206	Jabra PRO 935 UC BT - CN	Dual Connectivity	5706991017519	
935-15-509-207	Jabra PRO 935 UC BT - KR	Dual Connectivity	5706991017526	